


# TERMO DYNAMIC TYPES




## FCT FLOOR CONVECTOR WITH FAN

### 24V DC FLOOR CONVECTORS, DIRECT-CURRENT VOLTAGE




**FCT20-09**

270×90×800-4800 mm  
 Q 75/65/20 °C: 394-4779 W  
 Q 55/45/20 °C: 226-2748 W  
 heating, 2 pipe system  
 page 12




**FCT40-09**

320×90×800-4800 mm  
 Q 75/65/20 °C: 578-7039 W  
 Q 55/45/20 °C: 345-4198 W  
 heating, 2 pipe system  
 page 13




**FCT20-11**

270×115×800-4800 mm  
 Q 75/65/20 °C: 401-4406 W  
 Q 55/45/20 °C: 228-2513 W  
 heating, 2 pipe system  
 page 14



**FCT40-11**


320×115×800-4800 mm  
 Q 75/65/20 °C: 738-8122 W  
 Q 55/45/20 °C: 435-4787 W  
 heating, 2 pipe system  
 page 15



**FCT41-12**


320×125×1200-3200 mm  
 Q 75/65/20 °C: 1238-4333 W  
 Q 55/45/20 °C: 736-2578 W  
 heating, cooling, 2 pipe system  
 page 16

### 230V AC FLOOR CONVECTORS, ALTERNATING-CURRENT VOLTAGE




**FCT20-09**

270×90×800-3600 mm  
 Q 75/65/20 °C: 488-3902 W  
 Q 55/45/20 °C: 280-2244 W  
 heating, 2 pipe system  
 page 24




**FCT40-09**

320×90×800-3600 mm  
 Q 75/65/20 °C: 762-6094 W  
 Q 55/45/20 °C: 434-3471 W  
 heating, 2 pipe system  
 page 25




**FCT20-11**

270×115×800-4800 mm  
 Q 75/65/20 °C: 457-4839 W  
 Q 55/45/20 °C: 264-2795 W  
 heating, 2 pipe system  
 page 26




**FCT40-11**

320×115×800-4800 mm  
 Q 75/65/20 °C: 834-8845 W  
 Q 55/45/20 °C: 482-5110 W  
 heating, 2 pipe system  
 page 27



**FCT20-08**

170×90×800-4800 mm  
 Q 75/65/20 °C: 450-4950 W  
 Q 55/45/20 °C: 260-2863 W  
 heating, 2 pipe system  
 page 23




**FCT41-12**

320×125×1200-3200 mm  
 Q 75/65/20 °C: 1444-5198 W  
 Q 55/45/20 °C: 855-3077 W  
 heating, cooling, 2 pipe system  
 page 28


Note: The values of Q-heating output above are valid for fan medium speed.

## FCK FLOOR CONVECTOR WITH NATURAL CONVECTION




**FCK20-09**

170×90×800-4800  
 Q 75/65/20 °C: 70-656 W  
 Q 55/45/20 °C: 34-318 W  
 heating, 2 pipe system  
 page 34




**FCK40-09**

320×90×800-4800 mm  
 Q 75/65/20 °C: 142-1323 W  
 Q 55/45/20 °C: 66-614 W  
 heating, 2 pipe system  
 page 34




**FCK80-09**

420×90×800-4800 mm  
 Q 75/65/20 °C: 175-1637 W  
 Q 55/45/20 °C: 82-768 W  
 heating, 2 pipe system  
 page 34




**FCK20-11**

170×115×800-4800 mm  
 Q 75/65/20 °C: 91-848 W  
 Q 55/45/20 °C: 44-407 W  
 heating, 2 pipe system  
 page 36




**FCK40-11**

320×115×800-4800 mm  
 Q 75/65/20 °C: 174-1624 W  
 Q 55/45/20 °C: 83-777 W  
 heating, 2 pipe system  
 page 36




**FCK80-11**

420×115×800-4800 mm  
 Q 75/65/20 °C: 230-2149 W  
 Q 55/45/20 °C: 111-1034 W  
 heating, 2 pipe system  
 page 36




**FCK20-14**

170×140×800-4800 mm  
 Q 75/65/20 °C: 94-875 W  
 Q 55/45/20 °C: 45-422 W  
 heating, 2 pipe system  
 page 38



**FCK40-14**

320×140×800-4800 mm  
 Q 75/65/20 °C: 186-1733 W  
 Q 55/45/20 °C: 87-812 W  
 heating, 2 pipe system  
 page 38



**FCK80-14**

420×140×800-4800 mm  
 Q 75/65/20 °C: 263-2451 W  
 Q 55/45/20 °C: 125-1169 W  
 heating, 2 pipe system  
 page 38